



**NOTES:**

1. THE USE OF CONTROLLED DENSITY FILL (CDF) OR LEAN CONCRETE OR CRUSHED 5/8" TOP COURSE GRAVEL IS ACCEPTABLE AND MAY BE USED FOR BACKFILL. IF SOIL BACKFILL IS USED, THE BACKFILL SHOULD MEET RICHLAND STANDARD SPECIFICATION SECTION 2.3.1B AND BE COMPACTED IN 8" LIFTS. IN-PLACE DENSITY TESTS SHOULD BE PERFORMED AT NOT MORE THAN 1 FT. INTERVALS TO DETERMINE COMPACTION. COMPACTION SHOULD MEET ASTM D-698. TO ACHIEVE THE FULL STRENGTH WIND LOADING, THE EXCAVATED AREA SHOULD BE AT LEAST 4 FT ON EACH SIDE. BECAUSE THE DEPTH OF THE EXCAVATION IS GREATER THAN 4 FT. ON EACH SIDE. BECAUSE THE DEPTH OF THE EXCAVATION IS GREATER THAN 4 FT., THE EXCAVATION WALLS MUST BE SLOPED AS REQUIRED BY STATE & FEDERAL REGULATIONS, IF PERSONNEL WILL BE REQUIRED TO ENTER THE EXCAVATION.

2. IF HOLES ARE AUGURED THEN AN ABSOLUTE MIN. OF A 24" DIA. AUGER MUST BE USED. BACKFILL PER NOTE 1.



**STREET LIGHTING  
DIRECT BURIED POLE  
30/40 FT**

PUBLIC WORKS ENGINEERING	
APPR. BY: PKR	DATE: 11.15
DRAWN BY: LD	DWG: SL-1
CAD FILE: 2015_SL1_11_2015	